

BK...RS Series

| select     | Inquiry Designation |       | FW    | Principal Dimensions |        |         | r       | C      | Co          | Cu    | nG Weight |
|------------|---------------------|-------|-------|----------------------|--------|---------|---------|--------|-------------|-------|-----------|
|            |                     |       |       | D                    | C      | Ct      |         |        |             |       |           |
| BK 1012 RS | 10 mm               | 14 mm | 12 mm | - mm                 | 0,4 mm | 4400 N  | 5100 N  | 650 N  | 17000 U/min | 4,3 g |           |
| BK 1414 RS | 14 mm               | 20 mm | 14 mm | 11,3 mm              | 0,8 mm | 7100 N  | 8500 N  | 1010 N | 1200 U/min  | 13 g  |           |
| BK1614-RS  | 16 mm               | 22 mm | 14 mm | 11,3 mm              | 0,8 mm | 7600 N  | 9700 N  | 1160 N | 11000 U/min | 15 g  |           |
| BK2018-RS  | 20mm                | 26 mm | 18 mm | 15,3 mm              | 0,8 mm | 12700 N | 20100 N | 2500 N | 8500 U/min  | 24 g  |           |
| BK2518-RS  | 25 mm               | 35 mm | 18 mm | 15,3 mm              | 0,8 mm | 15600 N | 24000 N | 3150 N | 7000 U/min  | 34 g  |           |