

HFO 600 Series

select Inquiry		Designation	d	E	H	M	A	B	B1	C	d2	H1	L	L1	S	S1	U	V	weight	Adapter sleeve	Fixed bearing	Floating bearing
HFO 610	45	210	95	50	270 mm	145 mm	92 mm	30 mm	58 mm	168 mm	150 mm	135 mm	M 16	3 mm	19 mm	30 mm	24 kg	H 2310	HFO 610 AF	HFO 610 AL		
HFO 610	45	210	95	50	270 mm	145 mm	92 mm	30 mm	58 mm	168 mm	150 mm	135 mm	M 16	3 mm	19 mm	30 mm	24 kg	H 2310	HFO 610 BF	HFO 610 BL		
HFO 611	50	233	100	50	290 mm	148 mm	95 mm	30 mm	65 mm	30 mm	65 mm	180 mm	M 16	3 mm	19 mm	33 mm	25 kg	H 2311	HFO 611 AF	HFO 611 AL		
HFO 611	50	233	100	50	290 mm	148 mm	95 mm	30 mm	65 mm	30 mm	65 mm	180 mm	M 16	3 mm	19 mm	33 mm	25 kg	H 2311	HFO 611 BF	HFO 611 BL		
HFO 612	55	230	110	55	290 mm	152 mm	100 mm	30 mm	70 mm	198 mm	170 mm	155 mm	M 16	5mm	19 mm	34 mm	26 kg	H 2312	HFO 612 AF	HFO 612 AL		
HFO 612	55	230	110	55	290 mm	152 mm	100 mm	30 mm	70 mm	198 mm	170 mm	155 mm	M 16	5mm	19 mm	34 mm	26 kg	H 2312	HFO 612 BF	HFO 612 BL		
HFO 614	60	260	125	50	330 mm	182 mm	110 mm	35 mm	80 mm	230 mm	180 mm	165 mm	M 20	5 mm	24 mm	40 mm	33 kg	H 2314	HFO 614 AF	HFO 614 AL		
HFO 614	60	260	125	50	330 mm	182 mm	110 mm	35 mm	80 mm	230 mm	180 mm	165 mm	M 20	5 mm	24 mm	40 mm	33 kg	H 2314	HFO 614 BF	HFO 614 BL		
HFO 616	70	290	140	85	360 mm	210 mm	135 mm	40 mm	95 mm	255 mm	214 mm	184 mm	M 20	5 mm	24 mm	40 mm	40 kg	H 2316	HFO 616 AF	HFO 616 AL		
HFO 616	70	290	140	85	360 mm	210 mm	135 mm	40 mm	95 mm	255 mm	214 mm	184 mm	M 20	5 mm	24 mm	40 mm	40 kg	H 2316	HFO 616 BF	HFO 616 BL		
HFO 618	80	317	155	95	400 mm	246 mm	165 mm	50 mm	104 mm	280 mm	240 mm	210 mm	M 24	5 mm	28 mm	45 mm	72 kg	H 2318	HFO 618 AF	HFO 618 AL		
HFO 618	80	317	155	95	400 mm	246 mm	165 mm	50 mm	104 mm	280 mm	240 mm	210 mm	M 24	5 mm	28 mm	45 mm	72 kg	H 2318	HFO 618 BF	HFO 618 BL		
HFO 620	90	347	170	90	420 mm	245 mm	170 mm	55 mm	115 mm	315 mm	270 mm	240 mm	M 24	8 mm	28 mm	45 mm	98 kg	H 2320	HFO 620 AF	HFO 620 AL		
HFO 620	90	347	170	90	420 mm	245 mm	170 mm	55 mm	115 mm	315 mm	270 mm	240 mm	M 24	8 mm	28 mm	45 mm	98 kg	H 2320	HFO 620 BF	HFO 620 BL		
HFO 622	100	415	190	100	500 mm	265 mm	175 mm	65 mm	130 mm	355 mm	290 mm	250 mm	M 30	8 mm	35 mm	45 mm	109 kg	H 2322	HFO 622 AF	HFO 622 AL		
HFO 622	100	415	190	100	500 mm	265 mm	175 mm	65 mm	130 mm	355 mm	290 mm	250 mm	M 30	8 mm	35 mm	45 mm	109 kg	H 2322	HFO 622 BF	HFO 622 BL		
HFO 624	110	450	200	115	540 mm	265 mm	185 mm	65 mm	140 mm	375 mm	306 mm	265 mm	M 30	8 mm	35 mm	50 mm	126 kg	H 2324	HFO 624 AF	HFO 624 AL		
HFO 624	110	450	200	115	540 mm	265 mm	185 mm	65 mm	140 mm	375 mm	306 mm	265 mm	M 30	8 mm	35 mm	50 mm	126 kg	H 2324	HFO 624 BF	HFO 624 BL		
HFO 626	115	470	215	120	560 mm	285 mm	210 mm	65 mm	150 mm	405 mm	320 mm	280 mm	M 30	8 mm	35 mm	50 mm	156 kg	H 2326	HFO 626 AF	HFO 626 AL		
HFO 626	115	470	215	120	560 mm	285 mm	210 mm	65 mm	150 mm	405 mm	320 mm	280 mm	M 30	8 mm	35 mm	50 mm	156 kg	H 2326	HFO 626 BF	HFO 626 BF		
HFO 628	125	510	230	120	630 mm	300 mm	220 mm	80 mm	165 mm	425 mm	340 mm	300 mm	M 30	8 mm	35 mm	60 mm	185 kg	H 2328	HFO 628 AF	HFO 628 AL		
HFO 628	125	510	230	120	630 mm	300 mm	220 mm	80 mm	165 mm	425 mm	340 mm	300 mm	M 30	8 mm	35 mm	60 mm	185 kg	H 2328	HFO 628 BF	HFO 628 BL		
HFO 630	135	545	245	150	650 mm	320 mm	240 mm	75 mm	175 mm	455 mm	350 mm	320 mm	M 30	10 mm	35 mm	65 mm	210 kg	H 2330	HFO 630 AF	HFO 630 AL		

HFO 600 Series

HFO 630	135	545	245	150	650 mm	320 mm	240 mm	75 mm	175 mm	455 mm	350 mm	320 mm	M 30	10 mm	35 mm	65 mm	210 kg	H 2330	HFO 630 BF	HFO 630 BL
HFO 632	140	590	260	150	720 mm	335 mm	250 mm	85 mm	190 mm	480 mm	370 mm	330 mm	M 36	10 mm	42 mm	70 mm	240 kg	H 2332	HFO 632 AF	HFO 632 AL
HFO 632	140	590	260	150	720 mm	335 mm	250 mm	85 mm	190 mm	480 mm	370 mm	330 mm	M 36	10 mm	42 mm	70 mm	240 kg	H 2332	HFO 632 BF	HFO 632 BL
HFO 634	150	600	275	160	730 mm	350 mm	260 mm	85 mm	197 mm	510 mm	378 mm	338 mm	M 36	12 mm	42 mm	70 mm	280 kg	H 2334	HFO 634 AF	HFO 634 AL
HFO 634	150	600	275	160	730 mm	350 mm	260 mm	85 mm	197 mm	510 mm	378 mm	338 mm	M 36	12 mm	42 mm	70 mm	280 kg	H 2334	HFO 634 BF	HFO 634 BL
HFO 636	160	670	305	180	820 mm	370 mm	280 mm	95 mm	210 mm	565 mm	404 mm	365 mm	M 36	12 mm	42 mm	80 mm	372 kg	H 2336	HFO 636 AF	HFO 636 AL
HFO 636	160	670	305	180	820 mm	370 mm	280 mm	95 mm	210 mm	565 mm	404 mm	365 mm	M 36	12 mm	42 mm	80 mm	372 kg	H 2336	HFO 636 BF	HFO 636 BL