

GAR...DO / GAL...DO



select	Inquiry	Designation		Dimensions														Cr	Cor Weight
		right-hand thread	left-hand thread	d	D	B	dk	d1	d2	d3	h	C1	α	l1	l2	l7	r1 s/min		
GAR6-DO	GAL6-DO	6 mm	14 mm	6 mm	10 mm	8 mm	21 mm	M 6	36 mm	4,4 mm	13 °	18 mm	46,5 mm	12 mm	0,3 mm	3400 N	6920 N	0,018 kg	
GAR8-DO	GAL8-DO	8 mm	16 mm	8 mm	13 mm	10,2 mm	24 mm	M 8	42 mm	6 mm	15 °	22 mm	54 mm	14 mm	0,3 mm	5500 N	12900 N	0,032 kg	
GAR10-DO	GAL10-DO	10 mm	19 mm	9 mm	16 mm	13,2 mm	29 mm	M 10	48 mm	7 mm	12 °	26 mm	62,5 mm	15 mm	0,3 mm	8150 N	20600 N	0,054 kg	
GAR12-DO	GAL12-DO	12 mm	22 mm	10 mm	18 mm	14,9 mm	34 mm	M12	54 mm	8 mm	11 °	28 mm	71 mm	18 mm	0,3 mm	10800 N	30100 N	0,086 kg	
GAR15-DO	GAL15-DO	15 mm	26 mm	12 mm	22 mm	18,4 mm	40 mm	M14	63 mm	10 mm	8 °	34 mm	83 mm	20 mm	0,3 mm	17000 N	41500 N	0,14 kg	
GAR17-DO	GAL17-DO	17 mm	30 mm	14 mm	25 mm	20,7 mm	46 mm	M16	69 mm	11 mm	10 °	36 mm	92 mm	23 mm	0,3 mm	21200 N	56500 N	0,2 kg	
GAR20-DO	GAL20-DO	20 mm	35 mm	16 mm	29 mm	24,1 mm	53 mm	M20x1,5	75 mm	13 mm	9 °	43 mm	104,5 mm	27 mm	0,3 mm	30000 N	75600 N	0,31 kg	
GAR25-DO	GAL25-DO	25 mm	42 mm	20 mm	35,5 mm	29,3 mm	64 mm	M24x2	94 mm	17 mm	7 °	53 mm	126 mm	32 mm	0,6 mm	48000 N	88200 N	0,56 kg	
GAR30-DO	GAL30-DO	30 mm	47 mm	22 mm	40,7 mm	34,2 mm	73 mm	M30x2	110 mm	19 mm	6 °	65 mm	146,5 mm	37 mm	0,6 mm	62000 N	119000 N	0,89 kg	
GAR35-DO-2RS	GAL35-DO-2RS	35 mm	55 mm	25 mm	47 mm	39,7 mm	82 mm	M36x3	140 mm	21 mm	6 °	82 mm	181 mm	42 mm	0,6 mm	80000 N	159000 N	1,4 kg	
GAR40-DO-2RS	GAL40-DO-2RS	40 mm	62 mm	28 mm	53 mm	45 mm	92 mm	M39x3	150 mm	23 mm	7 °	86 mm	196 mm	48 mm	0,6 mm	100000 N	194000 N	1,8 kg	
GAR45-DO-2RS	GAL45-DO-2RS	45 mm	68 mm	32 mm	60 mm	50,7 mm	102 mm	M42x3	163 mm	27 mm	7 °	94 mm	214 mm	52 mm	0,6 mm	127000 N	259000 N	2,6 kg	
GAR50-DO-2RS	GAL50-DO-2RS	50 mm	75 mm	35 mm	66 mm	55,9 mm	112 mm	M45x3	185 mm	30 mm	6 °	107 mm	241 mm	60 mm	0,6 mm	156000 N	313000 N	3,4 kg	
GAR60-DO-2RS	GAL60-DO-2RS	60 mm	90 mm	44 mm	80 mm	66,8 mm	135 mm	M52x3	210 mm	38 mm	6 °	115 mm	277,5 mm	75 mm	1 mm	245000 N	485000 N	5,9 kg	
GAR70-DO-2RS	GAL70-DO-2RS	70 mm	105 mm	49 mm	92 mm	77,8 mm	160 mm	M56x4	235 mm	42 mm	6 °	125 mm	315 mm	87 mm	1 mm	315000 N	564000 N	8,2 kg	
GAR80-DO-2RS	GAL80-DO-2RS	80 mm	120 mm	55 mm	105 mm	89,4 mm	180 mm	M64x4	270 mm	47 mm	6 °	140 mm	360 mm	100 mm	1 mm	400000 N	689000 N	12 kg	